K-HOLE

Gabi Peretto

K-Hole System is aimed at satisfying the needs of lighting design planning particularly for retail spaces. The family is composed of two typologies: semi-recessed and ceiling/ wall with QR111 LED or halogen sources. The semi-recessed version can be installed in all plasterboard ceiling. In the wall/ceiling version, the power supply is integrated. Products realized in matt white powder coated aluminium.



LAMPING

Source Total power Emission Switching Tension Materials Notes Net lamp weight

Codes KH1 HWW 41

PACKAGE

Package 01


Certificazioni CEERE


G53 QR111
60W
orientable
dimmable TRIAC, according to bulb
230V
Aluminium
90° orientable bulb, drivers and trafos included
1 kg

Structure

white

Dimension: 16x18x15 cm / Gross weight: 1,5 kg





LED

LAMPING

Source Total power Emission Tension Materials Notes Net lamp weight

Codes KH1 LWW 41

PACKAGE

Package 01


Certificazioni CEERE


G53 QR111
30W
orientable
230V
Aluminium
90° orientable bulb, drivers and trafos included
1 kg

Structure

white

Dimension: 16x18x15 cm / Gross weight: 1,5 kg





LED/HALO RECESSED

CEILING/WALL

SEMIRECESSED

LAMPING

Source Total power Emission Switching Tension Materials Notes

Net lamp weight

Codes KH1 LWW 71

PACKAGE Package 01

Certificazioni

C€ ERE

G53 QR111 30W LED/60W HALO orientable dimmable TRIAC, according to bulb 230V Aluminium 90° orientable bulb, drivers and trafos included, recessed hole Ø8, Hmin 5cm 1,5 kg

Structure

white

Dimension: 15x18x16 cm / Gross weight: 2 kg

