

# PANZERI

## GINEVRA

220-240V AC tunable white  
P09280.050.9017

Ceiling or wall lighting fixture for interiors, with direct light emission.  
Turned aluminium structure in matt black and gold or white and gold polyacrylic paint.  
Pickled sheet metal wiring support plate in polyacrylic paint.  
Moulded polycarbonate micro-prismatic diffuser.



### Data sheet

CODE	P09280.050.9017
SYSTEM POWER CONSUMPTION	30W
EFFICACY	59.8lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	2700-6500K Ra>90
LIGHT DISTRIBUTION	Diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	Tunable White
DRIVER	Integrated Included
NOMINAL LUMINOUS FLUX	2963lm Min. / 3380lm Max
LUMEN OUTPUT	1794lm Min. / 2046lm Max
EFFICIENCY	60.547%
WEIGHT	5,5300Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS (CM)	20 x 62 x 62




### Finish

Black/gold



Technical drawing



$$\frac{11}{4\frac{1}{3}}''$$

$$\frac{53}{20\frac{7}{8}}''$$

---

# PANZERI

## GINEVRA

220-240V AC dimmable (DALI/Push DIM)  
P09280.080.0402

Ceiling or wall lighting fixture for interiors, with direct light emission.  
Turned aluminium structure in matt black and gold or white and gold polyacrylic paint.  
Pickled sheet metal wiring support plate in polyacrylic paint.  
Moulded polycarbonate micro-prismatic diffuser.



### Data sheet


CODE	P09280.080.0402
SYSTEM POWER CONSUMPTION	71W
EFFICACY	94.97lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	Diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	Dimmable (DALI/Push DIM)
DRIVER	Integrated Included
NOMINAL LUMINOUS FLUX	8857lm
LUMEN OUTPUT	6743lm
EFFICIENCY	76.132%
WEIGHT	10,9500Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS (CM)	1 x 90 x 90

### Finish

Black/gold



Technical drawing



14  
5 1/2"

80

31 1/2"

---