

DRAGSTER-T

Dragster-T is a recessed LED spot for interior applications.

Decorative rim made of varnished white aluminium (RAL 9016). It is available in “dark light” version with recessed optic to reduce glare.

There are three different beam angles and two colour temperatures.



3000K | 21°

LAMPING

Source	LED spot
Total power	13W
Emission	Direct 21°
Tension	350mA
Color temperature	3000K
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	40
Dimensions	8,2x8,2x7,8cm
Materials	Aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Accessories	Drivers 350mA,
Net lamp weight	0,315 kg

Codes

MDRGT101502WBO

Structure

white


PACKAGE

Package 01 Dimension: 15x10x9,3 cm / Gross weight: 0,33 kg

Certificazioni



DRAGSTER-T




| 7,8 |



| Ø 8,2 |

DRAGSTER-T / DARK LIGHT OPTIC



| 8,8 |



| Ø 8,2 |

3000K | 35°

LAMPING

Source	LED spot
Total power	13W
Emission	Direct 35°
Tension	350mA
Color temperature	3000K
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	40
Dimensions	8,2x8,2x7,8cm
Materials	Aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Net lamp weight	0,315 kg

Codes

MDRGT101802WBO

Structure

white


PACKAGE

Package 01 Dimension: 15x10x9,3 cm / Gross weight: 0,33 kg

Certificazioni



DRAGSTER-T




| 7,8 |



| Ø 8,2 |

DRAGSTER-T / DARK LIGHT OPTIC



| 8,8 |



| Ø 8,2 |

3000K | 50°

LAMPING

Source	LED spot
Total power	13W
Emission	Direct 50°
Tension	350mA
Color temperature	3000K
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	40
Dimensions	8,2x8,2x7,8cm
Materials	Aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Net lamp weight	0,315 kg

Codes

MDRGT101102WBO

Structure

white


PACKAGE

Package 01 Dimension: 15x10x9,3 cm / Gross weight: 0,33 kg

Certificazioni



DRAGSTER-T




| 7,8 |



| Ø 8,2 |

DRAGSTER-T / DARK LIGHT OPTIC



| 8,8 |



| Ø 8,2 |

4000K | 21°

LAMPING

Source	LED spot
Total power	13W
Emission	Direct 21°
Tension	350mA
Color temperature	4000K
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	40
Dimensions	8,2x8,2x7,8cm
Materials	Aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Net lamp weight	0,315 kg

Codes

MDRGT101502NBO

Structure

white


PACKAGE

Package 01 Dimension: 15x10x9,3 cm / Gross weight: 0,33 kg

Certificazioni



DRAGSTER-T




| 7,8 |



| Ø 8,2 |

DRAGSTER-T / DARK LIGHT OPTIC



| 8,8 |



| Ø 8,2 |

4000K | 35°

LAMPING

Source	LED spot
Total power	13W
Emission	Direct 35°
Tension	350mA
Color temperature	4000K
Luminous flux	1000°
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	40
Dimensions	8,2x8,2x7,8cm
Materials	Aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Net lamp weight	0,315 kg

Codes

MDRGT101802NBO

Structure

white


PACKAGE

Package 01 Dimension: 15x10x9,3 cm / Gross weight: 0,33 kg

Certificazioni



DRAGSTER-T




| 7,8 |



| Ø 8,2 |

DRAGSTER-T / DARK LIGHT OPTIC



| 8,8 |



| Ø 8,2 |

4000K | 50°

LAMPING

Source	LED spot
Total power	13W
Emission	Direct 50°
Tension	350mA
Color temperature	4000K
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	40
Dimensions	8,2x8,2x7,8cm
Materials	Aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Net lamp weight	0,315 kg

Codes

MDRGT101102NBO

Structure

white


PACKAGE

Package 01 Dimension: 15x10x9,3 cm / Gross weight: 0,33 kg

Certificazioni



DRAGSTER-T




| 7,8 |



| Ø 8,2 |

DRAGSTER-T / DARK LIGHT OPTIC



| 8,8 |



| Ø 8,2 |

DARK-LIGHT OPTIC | 3000K - 21°

LAMPING

Source	LED spot
Total power	13W
Emission	Direct 21°
Tension	350mA
Color temperature	3000K
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	40
Dimensions	8,2x8,2x8,8cm
Materials	Aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Net lamp weight	0,315 kg

Codes

MDRGTD01502WBO

Structure

white


PACKAGE

Package 01 Dimension: 15x10x9,3 cm / Gross weight: 0,33 kg

Certificazioni



DRAGSTER-T




| 7,8 |



| Ø 8,2 |

DRAGSTER-T / DARK LIGHT OPTIC



| 8,8 |



| Ø 8,2 |

DARK-LIGHT OPTIC | 3000K - 35°

LAMPING

Source	LED spot
Total power	13W
Emission	Direct 35°
Tension	350mA
Color temperature	3000K
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	40
Dimensions	8,2x8,2x8,8cm
Materials	Aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Net lamp weight	0,315 kg

Codes

MDRGTD01802WBO

Structure

white


PACKAGE

Package 01 Dimension: 15x10x9,3 cm / Gross weight: 0,33 kg

Certificazioni



DRAGSTER-T




| 7,8 |



| Ø 8,2 |

DRAGSTER-T / DARK LIGHT OPTIC



| 8,8 |



| Ø 8,2 |

DARK-LIGHT OPTIC | 3000K - 50°

LAMPING

Source	LED spot
Total power	13W
Emission	Direct 50°
Tension	350mA
Color temperature	3000K
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	40
Dimensions	8,2x8,2x8,8cm
Materials	Aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Net lamp weight	0,315 kg

Codes

MDRGTD01102WBO

Structure

white


PACKAGE

Package 01 Dimension: 15x10x9,3 cm / Gross weight: 0,33 kg

Certificazioni



DRAGSTER-T




| 7,8 |



| Ø 8,2 |

DRAGSTER-T / DARK LIGHT OPTIC



| 8,8 |



| Ø 8,2 |

DARK-LIGHT OPTIC | 4000K - 21°

LAMPING

Source	LED spot
Total power	13W
Emission	Direct 21°
Tension	350mA
Color temperature	4000K
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	40
Dimensions	8,2x8,2x8,8cm
Materials	Aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Net lamp weight	0,315 kg

Codes

MDRGTD01502NBO

Structure

white


PACKAGE

Package 01 Dimension: 15x10x9,3 cm / Gross weight: 0,33 kg

Certificazioni



DRAGSTER-T




| 7,8 |



| Ø 8,2 |

DRAGSTER-T / DARK LIGHT OPTIC



| 8,8 |



| Ø 8,2 |

DARK-LIGHT OPTIC | 4000K - 35°

LAMPING

Source	LED spot
Total power	13W
Emission	Direct 35°
Tension	350mA
Color temperature	4000K
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	40
Dimensions	8,2x8,2x8,8cm
Materials	Aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Net lamp weight	0,315 kg

Codes

MDRGTD01802NBO

Structure

white


PACKAGE

Package 01 Dimension: 15x10x9,3 cm / Gross weight: 0,33 kg

Certificazioni



DRAGSTER-T




| 7,8 |



| Ø 8,2 |

DRAGSTER-T / DARK LIGHT OPTIC



| 8,8 |



| Ø 8,2 |

DARK-LIGHT OPTIC | 4000K - 50°

LAMPING

Source	LED spot
Total power	13W
Emission	Direct 50°
Tension	350mA
Color temperature	4000K
Initial luminaire efficacy	70lm/W
Initial chromaticity	SDCM < 3
Typ cri	90
Energy class	A+
Ip class	40
Dimensions	8,2x8,2x8,8cm
Materials	Aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Net lamp weight	0,315 kg

Codes

MDRGTD01102NBO

Structure

white


PACKAGE

Package 01 Dimension: 23,5x15x11 cm / Gross weight: 1,23 kg

Certificazioni



DRAGSTER-T




| 7,8 |



| Ø 8,2 |

DRAGSTER-T / DARK LIGHT OPTIC



| 8,8 |



| Ø 8,2 |