

# Flock of Light


STUDIO TOER



Flock of Light, by Studio Toer, transforms from a light and airy artistic design piece at daytime, to a swarm of bright lights at night. Flock of Light comes in two sizes: 11 and 21, after the number of light sources. Both sizes are made from brass cups, bronze wires and semi-transparent polycarbonate diffusers. This suspension lamp brings a bright, warm and poetic glow right after dark. A Flock of Light captured in stillness.

---

## *Detailing*



Like standing amidst a swarm of buzzing bright lights. Flock of Light captures the magic of a warm summer evening.

# Flock of Light / 11

## Dimensions

80cm | 31.5"



65cm | 25.6"

65cm | 25.6"



## Product

**WIDTH** 80cm | 31.5"  
**HEIGHT** 65cm | 25.6"  
**DEPTH** 65cm | 25.6"  
**WEIGHT NETTO** 0.9kg | 1.98lbs

## Packaging

**WIDTH** 57cm | 22.4"  
**HEIGHT** 57cm | 22.4"  
**CUBAGE** 0.21m<sup>3</sup> | 7.34ft<sup>3</sup>  
**LENGTH** 64cm | 25.2"  
**WEIGHT** 2.5kg | 5.51lbs

## Technical CE

### MATERIAL

bronze wires, brass cups with semi-transparent polycarbonate diffusers

### ENERGY LABEL

Energy Label A+

### LIGHTSOURCE TYPE

LED

### NUMBER OF LIGHTSOURCES

11

### INPUT VOLTAGE

220-240

### MAX POWER CONSUMPTION

13W

### LAMPHOLDER

LED (Solid state)

### CABLE COLOUR

Transparent with tinned cores

### CANOPY

Pebble II White, ABS

### CRI

91

### LIGHT OUTPUT

1240 lm

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE INCLUDED

Yes

### SHAPE

Abstract

### FREQUENCY

50/60

### DIMMABLE

Yes

### LIFETIME

50000 hours

### CABLE LENGTH

250cm | 98.4"

### COLOUR TEMPERATUE

2700 K

### LIGHT DIRECTION

All directions

## Technical cULus

### MATERIAL

bronze wires, brass cups with semi-transparent polycarbonate diffusers

### ENERGY LABEL

Energy Label A+

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

11

### SHAPE

Abstract

### INPUT VOLTAGE

110-130

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

13W

### DIMMABLE

Yes

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Transparent with tinned cores

### CABLE LENGTH

250cm | 98.4"

### CANOPY

Pebble II White, ABS

### COLOUR TEMPERATUE

2700 K

### CRI

91

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

1240 lm

## Flock of Light / 21

### Dimensions

135cm | 53.2"

85cm | 33.5"



### Product

**WIDTH** 135cm | 53.1"

**HEIGHT** 65cm | 25.6"

**DEPTH** 85cm | 33.5"

**WEIGHT NETTO** 1.4kg | 3.09lbs

### Packaging

**WIDTH** 77cm | 30.3"

**HEIGHT** 57cm | 22.4"

**CUBAGE** 0.48m<sup>3</sup> | 17.05ft<sup>3</sup>

**LENGTH** 110cm | 43.3"

**WEIGHT** 4kg | 8.82lbs

## Technical CE

### MATERIAL

bronze wires, brass cups with semi-transparent polycarbonate diffusers

### ENERGY LABEL

Energy Label A+

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

21

### SHAPE

Abstract

### INPUT VOLTAGE

220-240

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

23W

### DIMMABLE

Yes

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Transparent with tinned cores

### CABLE LENGTH

250cm | 98.4"

### CANOPY

Pebble II White, ABS

### COLOUR TEMPERATUE

2700 K

### CRI

91

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

2308 lm

---

## Technical cULus

### MATERIAL

bronze wires, brass cups with semi-transparent polycarbonate diffusers

### ENERGY LABEL

Energy Label A+

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

21

### SHAPE

Abstract

### INPUT VOLTAGE

110-130

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

23W

### DIMMABLE

Yes

**LAMPHOLDER**

LED (Solid state)

**CABLE COLOUR**

Transparent with tinned cores

**CANOPY**

Pebble II White, ABS

**CRI**

91

**LIGHT OUTPUT**

2308 lm

**LIFETIME**

50000 hours

**CABLE LENGTH**

250cm | 98.4"

**COLOUR TEMPERATURE**

2700 K

**LIGHT DIRECTION**

All directions

---

## *Dimmer*

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

**DIMMER TYPE**

Mains dimmable (trailing edge / reverse phase)

**LOAD TYPE**

Capacitive load (C-Type)

---