

CAMALED SYSTEM

Camaled System is Modular tunable white LED system for interior applications.

Natural or black anodized aluminum body provided in different lengths. Modular LED high emission in variable colour temperature from 3000K to 4000K, turnable and dimmable. Camaled System is available with sanded or transparent screen. Dimmable 1...10V or with DMX Console.



TUNABLE WHITE | 1M

LAMPING

Source	Linear LED
Total power	15W
Emission	Diffused
Tension	12VDC
Color temperature	3000K - 4000K
Luminous flux	680lm
Initial luminaire efficacy	> 45lm/W
Initial chromaticity	SDCM < 3
Typ cri	> 94
Energy class	A+
Ip class	40
Dimensions	99x2,2x1cm
Materials	Anodized aluminum
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Customization options	Lengths
Accessories	Drivers 12VDC + DALI interface,
Net lamp weight	0,3 kg

Codes

BCAM0410G27EAA

Structure

grey

PACKAGE

Package 01

Dimension: 200x5x5 cm / Gross weight: 0,6 kg

Certificazioni



TUNABLE WHITE | 2M

LAMPING

Source	Linear LED
Total power	30W
Emission	Diffused
Tension	12VDC
Color temperature	3000K - 4000K
Initial luminaire efficacy	> 45lm/W
Initial chromaticity	SDCM < 3
Typ cri	> 94
Energy class	A+
Ip class	40
Dimensions	199x2,2x1cm
Materials	Anodized aluminum
Ambient temperature range	-20°C / 40°C
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Accessories	Drivers 12VDC + DALI interface,
Net lamp weight	0,6 kg

Codes

BCAM0420G27EAA

Structure

grey

PACKAGE

Package 01 Dimension: 300x5x5 cm / Gross weight: 0,9 kg

Certificazioni



TUNABLE WHITE | 3M

LAMPING

Source	Linear LED
Total power	45W
Emission	Diffused
Tension	12VDC
Color temperature	3000K - 4000K
Initial luminaire efficacy	70lm/W
Initial chromaticity	SDCM < 3
Typ cri	> 94
Energy class	A+
Ip class	40
Dimensions	299x2,2x1cm
Materials	Anodized aluminum
Ambient temperature range	-20°C / 40°C
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included
Accessories	Drivers 12VDC + DALI interface,
Net lamp weight	0,9 kg

Codes

BCAM0430G27EAA

Structure

grey

PACKAGE

Package 01 Dimension: 32x30x12,5 cm / Gross weight: 1,32 kg

Certificazioni

