



Arrangements Round Large

by Michael Anastassiades , 2018

Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.5m





Mounting	Pendant
Environment	Indoor
Weight	1.3 Kg
Light sources available	1 x FLEX STRIP LED 54W 2751lm 2700K CRI90 [i]
Emergency	Without
Voltage	48V
Power	54W
Battery	No
Supply included	No

Cord Length	2500 mm
Materials	Aluminum


Colors	● F0408030 - Black
--------	--------------------

Certificate	  
-------------	--




Arrangements Round Large

by Michael Anastassiades , 2018




F0415030

Big Rose-MAX190W




F0416030

Small Rose-MAX70



F0418030

Recessed Rose-MAX190W



Arrangements Round Small

by Michael Anastassiades , 2018


Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.5m




Mounting	Pendant
Environment	Indoor
Weight	0.5 Kg
Light sources available	1 x FLEX STRIP LED 21W 1068lm 2700K CRI90 [i]
Emergency	Without
Voltage	48V
Power	21W
Battery	No
Supply included	No

Cord Length	2500 mm
Materials	Aluminum

Colors	● F0406030 - Black
--------	--------------------

Certificate	  
-------------	--




Arrangements Round Small


by Michael Anastassiades , 2018



F0415030
Big Rose-MAX190W



F0416030
Small Rose-MAX70



F0418030
Recessed Rose-MAX190W