



Arrangements Drop Up

by Michael Anastassiades , 2018



Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.5m




Mounting	Pendant
Environment	Indoor
Weight	0.5 Kg
Light sources available	1 x FLEX STRIP LED 32W 1530lm 2700K CRI90 [i]
Emergency	Without
Voltage	48V
Power	32W
Battery	No
Supply included	No
Cord Length	2500 mm
Materials	Aluminum
Colors	● F0414030 - Black
Certificate	<div> <div>CE</div> <div>IP20</div> <div>III</div> </div>

Arrangements Drop Up


by Michael Anastassiades , 2018



F0415030
Big Rose-MAX190W



F0416030
Small Rose-MAX70



F0418030
Recessed Rose-MAX190W



Arrangements Drop Down

by Michael Anastassiades , 2018



Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.




Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.5m




Mounting	Pendant
Environment	Indoor
Weight	0.5 Kg
Light sources available	1 x FLEX STRIP LED 30W 1530lm 2700K CRI90 [i]
Emergency	Without
Voltage	48V
Power	30W
Battery	No
Supply included	No
Cord Length	2500 mm
Materials	Aluminum
Colors	● F0413030 - Black
Certificate	  

Arrangements Drop Down


by Michael Anastassiades , 2018



F0415030
Big Rose-MAX190W



F0416030
Small Rose-MAX70



F0418030
Recessed Rose-MAX190W