



Date

Name

Client

Project name

Quote #



Type / Quantity

29/05/2020 10:12:32

Specification Sheet

INFORM SQ P282-10 DOWN-UP 84067 25522 8420

[Weblink](#)



Available colors:

BLACK-BLACK (25522 8420 B-B)
BLACK-GOLD MATT (25522 8420 B-MMAT)
WHITE-BLACK (25522 8420 W-B)
WHITE-WHITE (25522 8420 W-W)

INCL. LED CLUSTER DOWN 34,0W / CRI>80 / 4000K / 6154lm
INCL. LED CLUSTER UP 27,2W / CRI>80 / 4000K / 4923lm
INCL. 120 x REFLECTOR FL-67° (DOWN)
EXCL. LED POWER SUPPLY 1800mA-DC
INCL. 3 x CABLE SUSPENSION SINGLE AUTO. 1,6m; INCL. 2 x CABLE SUSPENSION SINGLE
AUTO. 1,6m
POWER VIA CABLE SUSPENSION
MELANOPIC LIGHT TECHNOLOGY

LED Technics: Light source: 11077 lm // 61 W // 181 lm/W
Luminaire: 8695 lm // 70 W // 124 lm/W

Class: III

Weight: 2.2 KG
Protection level: IP20
Minimum distance: n.a.

Requirements: INFORM SQ POWERBOX 75W (DIM5)


For detailed installation instructions, please consult the manual.

INFORM SQ P282-10 DOWN-UP 84067
25522 8420

Related references


LED POWER SUPPLIES

[Weblink / Specs sheet](#)



INFORM SQ POWERBOX 75W
25510 0020
220-240V / 0|50-60Hz

[Weblink / Specs sheet](#)



INFORM SQ POWERBOX 75W DIM5
25510 0025
220-240V / 0|50-60Hz

Date

Name

Client

Project name

Quote #



Type / Quantity

29/05/2020 10:12:19

Specification Sheet

INFORM SQ P282-10 DOWN-UP 83067
25522 8320

[Weblink](#)



Available colors:

BLACK-BLACK (25522 8320 B-B)
 BLACK-GOLD MATT (25522 8320 B-MMAT)
 WHITE-BLACK (25522 8320 W-B)
 WHITE-WHITE (25522 8320 W-W)

INCL. LED CLUSTER DOWN 34,0W / CRI>80 / 3000K / 5882lm
 INCL. LED CLUSTER UP 27,2W / CRI>80 / 3000K / 4706lm
 INCL. 120 x REFLECTOR FL-67° (DOWN)
 EXCL. LED POWER SUPPLY 1800mA-DC
 INCL. 3 x CABLE SUSPENSION SINGLE AUTO. 1,6m; INCL. 2 x CABLE SUSPENSION SINGLE
 AUTO. 1,6m
 POWER VIA CABLE SUSPENSION
 MELANOPIC LIGHT TECHNOLOGY

LED Technics: Light source: 10588 lm // 61 W // 173 lm/W
 Luminaire: 8312 lm // 70 W // 118 lm/W

Class: III

Weight: 2.2 KG

Protection level: IP20

Minimum distance: n.a.

Requirements: INFORM SQ POWERBOX 75W (DIM5)


For detailed installation instructions, please consult the manual.

INFORM SQ P282-10 DOWN-UP 83067
25522 8320

Related references


LED POWER SUPPLIES

[Weblink / Specs sheet](#)



INFORM SQ POWERBOX 75W
25510 0020
220-240V / 0|50-60Hz

[Weblink / Specs sheet](#)



INFORM SQ POWERBOX 75W DIM5
25510 0025
220-240V / 0|50-60Hz