

Date

Name

Client

Project name

Quote#

Type/Quantity


28/05/2020 17:39:58

Specification Sheet

MANTELLO L2028 LED 927 DIM8

25815 9208

[Weblink](#)



Available colors: BLACK BRONZE (25815 9208 BBR)
RAW WHITE (25815 9208 RW)

INCL. 1 x LED 10,4W / CRI>90 / 2700K / 1032lm
INCL. 1 x CABLE 3 x 0.75mm² 1,6m
INCL. 1 x CABLE SUSPENSION SINGLE AUTOM. 1,6m
INCL. DIMMABLE LED POWER SUPPLY 500mA-DC
MAINS DIMMING - TRAILING EDGE

LED Technics: Light source: 1032 lm // 10 W // 105 lm/W
Luminaire: 12 W

220-240V / 50-60Hz

Class: I

Weight: 0.8 KG
Protection level: IP20
Minimum distance: n.a.


Requirements: CEILING BASE 1RC
CEILING BASE 3ROC

For detailed installation instructions, please consult the manual.

MANTELLLO L2028 LED 927 DIM8
25815 9208


Related references
CEILING BASES

[Weblink / Specs sheet](#)



CEILING BASE 1RC
23943 0030

[Weblink / Specs sheet](#)



CEILING BASE 3ROC
23943 0020

Date

Name

Client

Project name

Quote#

Type/Quantity


26/05/2020 18:26:50

Specification Sheet

MANTELLO L1520 LED 927 DIM8

25812 9208

[Weblink](#)



Available colors: BLACK BRONZE (25812 9208 BBR)
RAW WHITE (25812 9208 RW)

INCL. 1 x LED 10,4W / CRI>90 / 2700K / 1032lm
INCL. 1 x CABLE 3 x 0.75mm² 1,6m
INCL. 1 x CABLE SUSPENSION SINGLE AUTOM. 1.6m
INCL. DIMMABLE LED POWER SUPPLY 500mA-DC
MAINS DIMMING - TRAILING EDGE

LED Technics: Light source: 1032 lm // 10 W // 105 lm/W
Luminaire: 12 W

220-240V / 50-60Hz

Class: I

Weight: 0.6 KG
Protection level: IP20
Minimum distance: n.a.


Requirements: CEILING BASE 1RC
CEILING BASE 3ROC

For detailed installation instructions, please consult the manual.

MANTELLO L1520 LED 927 DIM8
25812 9208


Related references
CEILING BASES

[Weblink / Specs sheet](#)



CEILING BASE 1RC
23943 0030

[Weblink / Specs sheet](#)



CEILING BASE 3ROC
23943 0020